



TT150 - RF ID

With TT150-RF ID you have the ideal solution for full A5 Print, Apply and RF ID-encoding – according to GS1 UHF Gen 2 standards and specifications!

The TT150 has the reliable, robust and easy to use design - as seen on all the Mectec family machines. It is proven to give you 24 hours reliable labelling for many years to come - even in the most harsh industrial environments!



Printer and applicator in right hand version



Labelling pallets or large boxes with A5 / A6 portrait or landscape labels



Handheld terminal TG300 (optional)



Printer Control Unit PCU III

TECHNICAL DATA

- Type of applicator:** Tamp/Tamp-Blow. The blow can be switched off
- Tamp size:** 150 x 210 mm
- Print speed:** Up to 275 mm/sec
- Resolution:** 8 or 12 dots/mm 200/300 DPI
- Interface:** 2 x RS232, 1 x RS485, 1 x USB 2.0 (Ethernet optional)
- RF ID System:** 868 and 915 MHz, dual frequency support. Full UHF Gen 2 Compliance Automatic or Custom Tag programming
- Overall dimensions:** 667 x 685 x 318 mm (l x h x w) - P & A
406 x 265 x 128 mm (l x h x w) - PCU III
- Controller functions:** On-Line and Stand alone operation, 2 x 20 characters display, 9 keys, 11 status LEDs. 24 inputs, 26 outputs. Real timelock, counters, date offsets and much more...!

FAST FACTS

- Printer:** 6" Thermal Transfer
- Application:** Side, top or bottom labelling
Stationary objects preferred
- Label size:** 110 x 110 - 150 x 210 mm
- Distance:** 0 - 360 mm

Available in both right- and left hand version!

ACCESSORIES

- TG300 - Handheld terminal
- Warning Low Level Media
- Cabinets
- Label Check in the Applicator Pad
- Flashlight/Beacon
- Check scanner
- Fixed or adjustable stands

Manufactured by:

Mectec Elektronik AB
Agnesfridsvägen 189, SE-213 75 Malmö, Sweden
P: +46 40 689 25 00 • F: +46 40 689 25 25
info@mectec.se • www.mectec.com

Distributed by: